

# Vivitek D755WTi

WXGA ultra-short-throw projector with built-in interactivity and a host of connectivity options



## Product Features

- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- Built-in IWB functionality turns any surface into an interactive whiteboard
  - Dual pen support for simultaneous use
- Delivers a large 80" to 100" image from a ultra-short distance
  - Helps prevent shadow obstruction and light glare in the presenter's eyes
- Bright 3300 ANSI lumens with a colorful 5000:1 contrast ratio
- Energy efficient lamps that last up to 10,000 hours (in economy mode)
- Network ready for integration and system administration via RJ45
- VGA-output for display on a secondary monitor
- Powerful 10W (x2) audio speaker
- Top-loading, cover for quick and easy lamp replacement
- Sealed optical engine, minimizing the impact of dust and smoke
- 3D ready with DLP Link and Blu-Ray 3D functionality
- Keypad lock prevents accidental system adjustments

## Product Photos



Product Specifications	
Display Type	DLP
Brightness	3300 ANSI Lumens
Native Resolution	WXGA (1280 x 800)
Maximum Resolution	UXGA (1600 x 1200)@60Hz
Contrast Ratio	5,000:1
Lamp Life and Type	5,000/10,000 Hours (Normal/Eco. Mode), 230W/200W
Throw Ratio	0.35:1
Image Size (Diagonal)	80" - 100"
Projection Distance	605mm -705mm
Projection Lens	Manual Focus
Zoom Ratio	Fixed Lens
Aspect Ratio	16:10 Native
Offset	120%
Keystone Correction	Vertical +/- 40° (+/- 40 Step)
Horizontal Frequency	15, 30 – 91.4kHz
Vertical Scan Rate	43 - 87Hz
Interactive Functionality	Yes (via Camera)
3D Ready	Yes (Supports DLP Link, Blu-Ray 3D)
Speakers	10W (x2)
Lens Shift Range	Limited Lens Shift
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.4,VGA-In (x2), S-Video, Composite, DisplayPort, Audio-In RCA, Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ45, 3D-Sync Out, RS-232, USB (Service), Mini USB (Type B)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (W x D x H)	287.7 x 374.5 x 126.6mm (11.3" x 14.7" x 4.9")
Weight	5kg (11lbs)
Noise Level	33dB/29dB (Normal/Eco. Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	280W (Normal Mode), 240W (Eco.. Mode), <0.5W (Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Interactive Pen (x2), Documentation Kit
Optional Accessories	Replacement Lamp, Remote

©2014 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

