

Large Venue Projector

Vivitek DW6035

Dual Lamp Projector with Unmatched Performance and Functionality



Features

- Dual-lamp engine design for a brighter image and operational reliability should one lamp go down
- 6000 ANSI Lumens and 3000:1 contrast ratio
- Native WXGA resolution with a maximum UXGA resolution
- DLP® and BrilliantColor™ technologies for detailed image quality
- Variety of connectivity options including: DVI, S-video, composite, component
- Enhanced color and display adjustments
- PC 3D compatibility with DLP® Link™
- Power lens shift for easy adjustment and movement
- Seven (7) interchangeable lens options for a variety of projection needs
- Interchangeable color wheels for diverse applications and installation requirements
- One touch quick release lens button
- Built-in 12V trigger for convenient control of projector screen
- Network-ready for integration and system administration via RJ45

Photos



Specifications

Display Type	Single 0.65" DLP Technology by TI
Brightness	6000 ANSI Lumens
Native Resolution	WXGA (1280 x 800)
Maximum Resolution	UXGA (1600 x 1200) @60Hz
Contrast Ratio	3,000:1
Lamp Life/Type	2000/2500 Hours (Normal/Eco. Mode), 280W x 2
Throw Ratio*	1.81-2.38:1
Image Size (Diagonal)*	40" - 500"
Projection Distance*	1.53 - 26.11 m (5.02ft to 85.66ft)
Projection Lens*	F = 1.7 - 1.9, f = 26 - 34 mm
Zoom Ratio*	1.3x
Aspect Ratio	16:10
Offset	Power Lens Shift
Keystone Correction	Vertical +/-30
Horizontal Frequency	15, 30 – 90Hz
Vertical Scan Rate	50 - 85Hz
3D Compatibility	Yes (PC 3D Compatibility via DLP® Link™)
Lens Shift Range*	Vertical: 0~50%, Horizontal: +/- 10%
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	VGA-In, DVI-D, Component (5 BNC) (RGBHV), Component (YPbPr RCA x 3), S-Video, Composite Video, VGA-Out, RJ45, 12V Trigger, RS-232C, USB (Service), Remote Jack (Wire Remote)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (WxDxH)	508 x 389 x 195 mm (20"x 15.3" x 7.7")
Weight	17 kg (37.5 lbs)
Available Colors	White
Noise Level	39dB/34dB (Standard/Economy Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	710W (Normal Mode), 570W (Eco. Mode), <0.5W (Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control w/Batteries, Lens Cap, Interchangeable Color Wheel, Documentation Kit
Optional Accessories	Replacement Lamp, Remote Control, Interchangeable Lens Options (x7)

*Note: Standard Lens

Optional Lenses	Standard Lens	Wide Zoom	Wide Fix	Semi Long Zoom
Lens Name	D88-ST001	D88-WZ01	D88-WF18501	D88-SMLZ01
Model No.	D88-ST001	D88-WZ01	D88-WF18501	D88-SMLZ01
F#	1.7 - 1.9	1.85-2.5	1.85	1.86-2.48
Focal Length	26-34mm	18.7-26.5mm	11.6mm	32.9-54.2mm
Zoom Ratio	1.3:1	1.4:1	--	1.65:1
Screen Size	40" - 500"	40" - 500"	40" - 500"	40" - 500"
Throw Ratio	1.81-2.38:1	1.31-1.87:1	0.8:1	2.33-3.86:1

Optional Lenses	Long Zoom 1	Long Zoom 2	Ultra Wide Zoom
Lens Name	D88-LZ01	D88-LZ02	D88-UW201
Model No.	D88-LOZ101	D88-LOZ201	D88-UW201
F#	1.85 - 2.41	1.85 - 2.48	1.96-2.3
Focal Length	52.8-79.1mm	78.5-121.9mm	11.3-14.1mm
Zoom Ratio	1.5:1	1.55:1	1.25:1
Screen Size	40" - 500"	40" - 500"	40" - 500"
Throw Ratio	3.76-5.64:1	5.56-8.67:1	0.78-0.99:1

©2014 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

