

Vivitek DU6871

Super Bright Large Venue Projector with 3D Capabilities



Features

- 7300 ANSI Lumens and 3000:1 contrast ratio
- Native WUXGA resolution with a maximum UXGA resolution
- DLP® and BrilliantColor™ technologies for detailed image quality
- Powered horizontal and vertical lens shift
- Dual-lamp engine design to create a brighter picture and operational reliability should one lamp go down
- Range of versatile inputs: HDMI v1.4a, DisplayPort, VGA-Out, RJ45 and RS232C
- DisplayPort connector for digital audio and video signals
- HDBaseT® interface with support for distribution of HD video and digital audio content over standard CAT5e/6 LAN cable
- 3D compatibility with DLP® Link™, and HDMI 1.4 technology support (Blu-ray, side by side, frame packing, top and bottom) for dazzling and realistic life-like images
- 3D sync port for compatibility with IR (infrared) 3D passive synchronization protocol
- Built-in 12V trigger for convenient control of projector screen
- Crestron® RoomView™ integration for network monitoring and management
- Seven (7) interchangeable lens options for greater installation flexibility
- Ani-theft security features include: Kensington® security slot, security bar, PIN lock keypad and anti-theft lens screw

Specifications

Display Type	Single 0.67" DLP Technology by TI
Brightness	7300 ANSI Lumens
Native Resolution	WUXGA (1920 x1200)
Maximum Resolution	WUXGA (1920 x 1200)@60Hz
Contrast Ratio	3,000:1
Lamp Life/Type	2000/2500 Hours (Normal/Eco. Mode), 350W x 2
Throw Ratio*	1.73 - 2.27 : 1
Image Size (Diagonal) *	40" - 500"
Projection Distance*	1.45 - 24.85 m (4.77ft to 81.52ft)
Projection Lens**	F = 1.7 - 1.9, f = 26 - 34mm
Zoom Ratio*	1.3x
Aspect Ratio	16:10
Offset	Power Lens Shift
Keystone Correction	Vertical +/-30
Horizontal Frequency	15, 30 – 90Hz
Vertical Scan Rate	50 - 85Hz
3D Compatibility	Yes (DLP® Link™, HDMI 1.4 (Blu-ray, side by side, frame packing, top and bottom))
Lens Shift Range*	Vertical: 0~50%, Horizontal: +/- 10%
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.4a, DisplayPort, DVI-D, Component (5 BNC) (RGBHV), RGB-In, RGB-Out, 12V Trigger, 3D Sync-Out, RS-232C, USB (Service), Remote Jack (Wire Remote), RJ45/HDBaseT® (Shared Port)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Pin Lock Keypad, Anti-Theft Lens Screw
Dimensions (WxDxH)	505 x 520 x 195mm (19.9"x 20.5" x 7.7")
Weight	20Kg (44.1 lbs)
Available Color	Black
Noise Level	Dual Lamp: 40dB/35dB (Normal/Economy Mode)
Power Supply	AC 110-240V, 50/60Hz
Power Consumption	Dual Lamp: 880W (Normal Mode), 630W (Eco. Mode), <0.5W (Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Lens Cap, Interchangeable Color Wheel, Documentation Kit
Optional Accessories	Replacement Lamp, Remote Control, Interchangeable Lens Options (x7)

*Note: Standard Lens

Photos



Optional Lenses

Lens Name	Standard Lens	Wide Zoom	Wide Fix	Semi Long Zoom
Model No.	D88-ST001	D88-WZ01	D88-WF18501	D88-SMLZ01
F#	1.7 - 1.9	1.85-2.5	1.85	1.86-2.48
Focal Length	26-34mm	18.7-26.5mm	11.6mm	32.9-54.2mm
Zoom Ratio	1.3:1	1.41:1	-	1.65:1
Screen Size	40" - 500"	40" - 500"	40" - 500"	40" - 500"
Throw Ratio	1.73-2.27:1	1.25-1.79:1	0.76:1	2.22-3.67:1

Lens Name	Long Zoom 1	Long Zoom 2	Ultra Wide Zoom
Model No.	D88-LOZ101	D88-LOZ201	D88-UW201
F#	1.85 - 2.41	1.85 - 2.48	1.96-2.3
Focal Length	52.8-79.1mm	78.5-121.9mm	11.3-14.1mm
Zoom Ratio	1.5:1	1.55:1	1.25:1
Screen Size	40" - 500"	40" - 500"	40" - 500"
Throw Ratio	3.58-5.38-1	5.31-8.26:1	0.75-0.93:1

©2013 Vivitek Corporation. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

