

Multimedia Projector

Vivitek D910HD

The 1080p cross-over projector for SOHO



Features

- 3000 ANSI lumens of brightness with a 5,000:1 contrast ratio
- Native 1080P (1920 x 1080) resolution with a maximum WUXGA (1920 x 1200) resolution
- DLP® and BrilliantColor™ technologies for detailed image quality
- High-efficiency lamps that last up to 5000 hours
- Connectivity options include: HDMI, DisplayPort, VGA-in (2x), VGA-Out, composite video, component video, S-video
- Direct 3D over HDMI
- 3D-ready via DLP® Link™ and BluRay 3D movie playback
- Network ready for integration and system administration via RJ45
- Audio ready with an internal 10W speaker
- Sealed optical engine, minimizing the impact of dust and smoke
- Top-loading, cover for quick and easy lamp replacement
- Fully featured remote control with laser pointer
- Security solutions include: Kensington® security slot, security bar, keypad lock

Specifications

Display Type	Single 0.65" DLP® Technology by TI
Brightness	3000 ANSI Lumens
Native Resolution	1080P (1920 x 1080)
Maximum Resolution	WUXGA 1920x1200@60 Hz
Contrast Ratio	5,000:1
Lamp Life/Type	3500/5000 Hours (Normal/Eco Mode), 240W/190W
Throw Ratio	1.58 - 1.92 : 1
Image Size (Diagonal)	23.5"-300"
Projection Distance	1 - 10m (3.28ft to 32.8ft)
Projection Lens	F=2.51~2.77, f = 23.5~28.2mm
Zoom Ratio	1.2x
Aspect Ratio	16:9
Offset	130% +/-10%
Keystone Correction	Vertical +/- 40°, +/- 40 Step
Horizontal Frequency	15, 31 ~ 91.4kHz
Vertical Frequency	24 ~ 30Hz, 47 ~ 120Hz
3D Functionality	Yes (Via DLP® Link™, BluRay 3D)
Speakers	10W (Mono)
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	VGA-In (x2), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ45, 12V-Trigger, RS-232, Mini-USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar
Dimensions (W x D x H)	285 x 261 x 121.8 mm (11.22" x 10.3" x 4.8")
Weight	3.15kgs (6.94 lbs)
Noise Level	35dB/32B (Normal/Eco Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	290W (Normal Mode), 240W (Eco. Mode), <0.5W (Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Carry Case, Lens Cap, Documentation Kit
Optional Accessories	Replacement Lamp, Remote Control, Carry Case

©2013 Vivitek Corporation. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.



Photos

