

Vivitek D555

High contrast ultra-portable projector



Product Features

- Native XGA resolution and with a high 3,000 ANSI lumens of brightness
- 15,000:1 contrast ratio for amazing picture quality
- DLP® BrilliantColor™ technologies for bright and vibrant color projection
- Up to 6,000 hours of lamp lifetime
- Full connectivity: HDMI v1.4, VGA-In, S-Video, Composite Video, and RS-232
- Environmentally friendly with less than 0.5W of power in stand-by mode
- Source filtering function to save time locating device signal source
- 3D ready with DLP Link and Blu-Ray 3D functionality
- Convenient top loading design for easy lamp replacement
- Keypad lock prevents accidental system adjustments
- Closed caption and rapid on/off feature
- 2.3kg/5lbs for easy portability

Product Photos



Product Specifications

Display Type	DLP® BrilliantColor™ Technology
Brightness	3000 ANSI Lumens
Native Resolution	XGA (1024 x 768)
Maximum Resolution	UXGA (1600 x 1200)@60Hz
Contrast Ratio	15,000:1
Uniformity	95%
Lamp Type	190W/160W (Normal/Eco Mode)
Lamp Life	5,000/6,000 Hours (Normal/Eco Mode)
Throw Ratio	1.92 - 2.14:1
Image Size (Diagonal)	23" - 256" (58 - 650cm)
Projection Distance	1 - 10m (3.28ft to 32.8ft)
Projection Lens	F = 2.52 - 2.73, f = 21.8 - 24mm
Zoom Ratio	1.1x
Aspect Ratio	4:3 Native
Offset	128% +/-10%
Keystone Correction	Vertical +/-40%, +/-40 Step
Horizontal Frequency	2D: 15, 30 - 91.4kHz/3D: 101.6KHz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
Speakers	2W (Mono)
3D Ready	Yes (Supports DLP Link, Blu-Ray 3D)
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.4, VGA-In (x2), S-Video, Composite Video, Audio-In (L/R), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Keypad Lock
Dimensions (W x D x H)	274.6 x 212 x 100mm (10.8" x 8.3" x 3.9")
Weight	2.3kg (5lbs)
Noise Level	35dB/32dB (Normal/Eco Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	200W (Eco. Mode), 240W (Normal Mode), <0.5W (Standby)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit
Optional Accessories	Replacement Lamp, Remote w/Laser Pointer

©2012 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

