

Vivitek ViviNet

Professional Wireless Presentation System

Features

- Turns any VGA enabled projector into a wireless ready presentation system
- Quick setup with auto-detection for easy plug and projection
- Complies with wireless 802.11b/g/n standards with data rate up to 150Mbps
- Supports 64/128-bit WEP, WPA , WPA2 encryption and WPS-compatible
- 4-to-1 split projection for increased productivity
- Wireless link coverage up to 100m away
- PoVGA support, so no need for an external power adapter
- Portable and compact design

Photos



Specifications

Model Number	ViviNet
Product Compatibility	Any Vivitek projector with 15-Pin VGA Port
Hardware Interface	15-Pin VGA, Reset Button
Web Management	Yes (Web-based configuration)
4-to-1 Split Projection	Yes
Standards	IEEE 802.11b/g/n 2.4GHz, IEEE 802.3 (10BASE-T)/IEEE 802.3u (100BASE-TX)
Wireless Data Rate	Up to 54Mbps
Supported Output Resolutions	SVGA (800 x 600), XGA (1024 x 768), WXGA (1280 x 768), WXGA+ (1280 x 800)
Security	IEEE Standard 64/128 bit WEP/WPA/WPA2-PSK
Wireless Link Coverage	Up to 300 feet/100 meters (Depends on environment)
Receiving Sensitivity	65dBm@54Mbps, 80dBm@11Mbps at 10-5 BER
Power	PoVGA Compliant, External Power Adapter (5V DC Input 1.2A)
Supported Operating Systems	Windows XP/Vista/7, Windows Mobile 5/6 (Mobishow), MAC OSx 10.5 and above
Safety/EMI Regulations	CE, FCC, NCC
Available Colors	Black
In-The-Box Accessories	Power Adapter, Documentation Kit
Dimensions (W x H x D)	92.3 x 40 x 22mm (3.6" x 1.6" x 0.89")
Weight	52.2g (0.07lbs)

© 2014 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.