

Multimedia Projector

Vivitek DX864

XGA projector with embedded media player



Features

- DLP® and BrilliantColor™ technologies from Texas Instruments
- XGA (1024 x 768) resolution with a maximum resolution up to UXGA (1600 x 1200)
- Powerful and easy to use multimedia utility(application) allows the projector to be controlled and monitored through a PC with a USB or network connection (RJ-45)
- Integrated media and document viewer conveniently plays documents, photos, videos and audio files without the need to connect a PC
- Assortment of connectivity options for easy connection to a variety of multimedia devices (HDMI, VGA, USB)
- 3D compatibility with DLP® Link™ for dazzling and realistic life-like images
- Built-in 10W audio speaker
- Crestron® RoomView™ integration for network monitoring and management
- Sealed optical engine, minimizing the impact of dust and smoke

Ani-theft security features include: Kensington® security slot, security bar, and PIN lock keypad

Photos



Specifications

Display Type	Single 0.55" DLP Technology by TI	
Brightness	3,500 ANSI Lumens	
Native Resolution	XGA (1024 x 768)	
Maximum Resolution	Up to UXGA (1600 x 1200)@60Hz	
Contrast Ratio	6,000:1	
Lamp Life/Type	3500/5000 Hours (Normal/Eco. Mode), 240W/190W	
Throw Ratio*	1.6 - 1.92:1 (61.5" @2m)	
Image Size (Diagonal)*	25.6" - 308"	
Projection Distance*	1 - 10m (3.28ft to 32.8ft)	
Projection Lens*	F#2.50-2.72, f=17.81-22.35mm	
Zoom Ratio*	1.2x	
Aspect Ratio	4:3 Native	
Offset	114% (JIS) / 128% +/- 10%	
Keystone Correction	+/-15 Degree; +/- 40 Steps	
Horizontal Frequency	15, 30 ~ 91.4kHz	
Vertical Scan Rate	43 ~ 87Hz	
Lens Shift Range*	N/A	
3D Compatibility	Yes (DLP® Link™)	
Audio	10W	
File Formats Supported	Documents	Microsoft® Office 97 - 2007 (DOC, PPT, XLS), Adobe® Reader (PDF), Text (TXT)
	Video	AVI, DIVX, MKV, TS, DAT, VOD, MPG, MPEG, MOV, MP4, RM, RMVB, WMV
	Image	JPEG, JPG, BMP
	Audio	MP1, MP2, MP3, WMA, OGG, ADPCM-WAV, PCM-WAV, AAC
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)	
I/O Connection Ports	HDMI v1.3, VGA-In (x2), Composite Video, Audio-In RCA (L/R), Audio-In (Mini-Jack), VGA-Out, USB (Type A), USB Mini-A, Audio-Out (Mini-Jack), RJ45, RS-232C, USB Mini-B (Service)	
Projection Method	Table Top, Ceiling Mount (Front or Rear)	
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock	
Dimensions (WxDxH)	285 x 261 x 121.8mm (11.22" x 10.3" x 4.8")	
Weight	3.15kg (6.94lbs)	
Available Color	White	
Noise Level	35dB/32dB (Normal/Eco. Mode)	
Power Supply	AC 110-240V, 50/60Hz	
Power Consumption	250W (Eco. Mode), 310W (Normal Mode), <0.5W (Standby Mode)	
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Lens Cap, Documentation Kit	
Optional Accessories	Wi-Fi USB Dongle, Replacement Lamp, Remote, Carrying Case	

©2014 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

