

Large Venue Projector

Vivitek DX3351

Small Foot Print Large Venue Projector with a Host of Connectivity Options



Features

- Up to 6,000 ANSI lumens for the ultimate projection in just about any environment
- Native XGA resolution with a maximum WUXGA support
- DLP® and BrilliantColor™ technologies from Texas Instruments
- Centered lens with horizontal and vertical lens shift for hassle-free installation
- Distorted and trapezoid image issues are easily corrected with keystone, 4-corner and pincushion controls
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- 3D sync port for compatibility with IR (infrared) 3D passive synchronization protocol
- Project 3D content from DLP® Link™ and Blu-ray HDMI
- 12V trigger port for direct communications and automated control of such devices as screens and curtains
- 14W of total 3D audio surround sound power (7W x 2) with multiple audio-in and audio-out ports
- Network ready for integration and system administration via RJ45
- Conveniently adjust the zoom and focus manually at the turn of a button
- Sealed engine to minimizing the impact of dust and smoke
- Top sided lamp cover for simple lamp removal and insertion
- Dual infrared sensors for handy remote control from either in front or behind the projector
- Anti-theft security features include: Kensington® security slot, and security bar

Photos



Specifications

Display Type	Single 0.7" DLP Technology by TI
Brightness	6,000 ANSI Lumens
Native Resolution	XGA (1024x768)
Maximum Resolution	WUXGA (1920x1200) @60Hz
Contrast Ratio	10,000:1
Lamp Life/Type	1,500/3,500 hours (Normal/Eco Mode) 370W/280W
Throw Ratio	1.32 - 2.24:1
Image Size (Diagonal)	22.3" - 378.6"
Projection Distance	1 - 10m (3.28ft - 32.8ft)
Projection Lens	F=2.45 - 3.22, f= 18.8mm - 32mm
Zoom Ratio	1.7x
Aspect Ratio	4:3
Offset	124.7%/112.3%
Keystone Correction	Vertical ±30°, Horizontal ±25°
Horizontal Frequency	15, 31 – 91.4kHz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
3D Functionality	Yes (Supports DLP® Link™, Blu-ray 3D)
Speakers	3D Audio Surround Sound (7W x 2)
Lens Shift Range	Vertical: -10.5%,+3% Horizontal: +/-3.8%
Computer Compatibility	GA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac
Video Compatibility	SDTV (480i, 576i)/EDTV (480p, 576p)/HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
I/O Connection Ports	HDMI v1.4b, MHL/HDMI v1.4, VGA-In (x2), DVI-D, Component (5 BNC) (RGBHV), S-Video, Composite Video, Audio-In RCA (L/R), Audio-In (Mini-Jack)(x3), Microphone-In (Mini-Jack), Wired Remote-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), Audio-Out RCA (L/R), 12v Screen Trigger (Mini-Jack), 3D Sync-Out, RS-232, USB Type A (File Reader/USB Host), USB Type B (Service), USB Display (MINI B), USB Type A (Wireless Dongle), Wired Remote-Out (Mini-Jack), RJ45
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar
Dimensions (W x D x H)	445 x 330.2 x 160.2mm (17.5"x 12.9" x 6.3")
Weight	8.4kg (18.5lbs)
Noise Level	36dB/30dB (Normal/Eco Mode)
Available Color	Dual Tone Color: White and Gray
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	480W (Normal Mode), 380W (Eco. Mode), <0.5W (Standby Mode), <6W (LAN Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Filter, Documentation Kit
Optional Accessories	Replacement Lamp, Wireless USB Dongle

©2015 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

