



Multimedia Projector

Vivitek DX83AAA

High brightness XGA Projector with MHL and a Host of Connectivity Options



- Bright 4,300 ANSI lumens with a high 18,000 contrast ratio
- Energy efficient lamps that last up to 4,000 hours (in Image Care mode)
- 6 Segment (RYGCWB) color wheel for accurate and detailed images
- Quick auto search filtering to quickly locate input signal source
- Variety of display connectivity options including: HDMI (x2), VGA-in (2x), VGA-Out, S-Video and Composite Video
- 3D compatibility with DLP® Link™ and HDMI 1.4b Blu-Ray support for dazzling and realistic life-like images
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- Compatible with long VGA cables for a maximum length up to 20 meters
- Enhanced environmentally friendly power functions (Eco mode, Auto power off, stand-by mode) to increase lamp life, power savings and energy consumption
- Internal audio speaker delivers 10W of total audio power
- Integrated network monitoring and management solutions (product certified) including Crestron® RoomView™, Extron, AMX SSSD and Telnet
- Top-loading, sliding cover for quick and easy lamp replacement
- Anti-theft security features include: Kensington® security slot, security bar, and PIN lock keypad

Specifications

Display Type	Single 0.55" DLP Technology by TI
Brightness	4,300 ANSI Lumens
Native Resolution	XGA (1024 x 768)
Maximum Resolution	WUXGA (1920x1200)@60Hz
Contrast Ratio	18,000:1
Lamp Life/Type	2500/3000/3500/4,000 Hours (Normal/Eco./Dynamic Eco./Dynamic Eco. Plus Mode), 310W/245W
Throw Ratio	1.83 - 2.75
Image Size (Diagonal)	21.5" - 269.7"
Projection Distance	1.2 - 10 m (3.94ft - 2.8ft)
Projection Lens	F=2.42 - 2.97, f=20.70 - 31.05mm
Zoom Ratio	1.5x
Aspect Ratio	4:3 Native
Offset (Vertical)	113.9±5%
Keystone Correction	±40 Degree; ±40 Steps
Horizontal Frequency	15, 31 - 91.4Hz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
3D Compatibility	Yes (DLP® Link™, HDMI 1.4b (Blu-Ray))
Audio	10W (Mono)
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60Hz, Mac
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
I/O Connection Ports	HDMI v1.4, MHL/HDMI v1.4, VGA-In (x2), S-Video, Composite Video, Audio-In (RCA L/R), Audio-In (Mini-Jack), VGA-Out, USB (Type A for 5V/1.5A Power Only), Audio-Out (Mini-Jack), RJ45, RS-232, Mini-USB (Service), Microphone (Mini-Jack), 12V Trigger
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (WxDxH)	314 x 216 x 126mm (12.5" x 8.5" x 4.9")
Weight	3.2kg (7lbs)
Available Color	Dual-Tone: White/Gray
Noise Level	38dB/34dB (Normal/Eco. Mode)
Power Supply	AC 110-240V, 50/60Hz
Power Consumption	320W (Eco. Mode), 410W (Normal Mode), <0.5W (Standby Mode), <2W (LAN Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Filter (China only), Documentation Kit
Optional Accessories	Replacement Lamp

©2015 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.



Photos

