



Large Venue Projector

Vivitek DU5671

High brightness professional-grade WUXGA projector with full connectivity and HDBaseT™



Features

- DLP and BrilliantColor™ technologies by Texas Instruments
- Up to 6,200 ANSI lumens with a 2,000:1 contrast ratio
- Native WUXGA resolution with a maximum WUXGA resolution
- Manual zoom and focus for easy adjustment and positioning flexibility
- Centered lens for easy installation
- Horizontal and vertical lens shift (manual) for greater installation convenience and flexibility
- Distorted and trapezoid image issues are easily corrected with H/V keystone, and 4-corner adjustment
- Full suite of display connectivity inputs and outputs including: HDMI v1.4b, DVI-D, Composite Video, S-Video, Component (5 BNC) (RGBHV), VGA-In, VGA-Out
- HDBaseT™ interface with support for distribution of HD video and digital audio content over standard CAT5e/6 LAN cable
- 3D compatibility with DLP® Link™ and HDMI 1.4 Blu-Ray technology support
- 3D sync port for compatibility with IR (infrared) 3D passive synchronization protocol
- RS-232c/RJ45 ready for integration and system automation
- Crestron® RoomView™ integration for network monitoring and management
- Seven (7) interchangeable lens options with quick touch lens release design for easy lens installation/removal
- Anti-theft security features include: Kensington® security slot, and security bar

FOR ASIA ONLY

Specifications

Display Type	Single Chip 0.67" DLP Technology by TI
Brightness	6,200 ANSI Lumens
Native Resolution	WUXGA (1920 x 1200) @60Hz
Maximum Resolution	WUXGA (1920 x 1200) @60Hz
Contrast Ratio	2,000:1
Lamp Life/Type	1,000/1,200 hours (Normal/Eco Mode), 430W/320W
Throw Ratio*	1.54 - 1.93:1
Image Size (Diagonal)*	36.1" - 300" (based on VL906G/LNS-5SZ12)
Projection Distance*	1.5m - 10m (4.9ft - 33ft)
Zoom Ratio*	1.25x
Aspect Ratio	16:10
Keystone Correction	Vertical ±30°, Horizontal ±30°
Horizontal Frequency	15, 31 - 91.4Hz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
3D	Yes (DLP® Link™, HDMI 1.4 (Blu-Ray 3D))
Speaker	3W (x1)
Lens Shift Range*	Vertical: -20%~+60%; Horizontal: +/-5%
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60Hz, Mac
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
I/O Connection Ports	HDMI v1.4b (x2), DVI-D, Composite Video, S-Video, Component (5 BNC) (RGBHV), VGA-In (x2), Audio-In RCA (L/R), Audio-In (Mini-Jack)(x2), Audio-Out (Mini-Jack), VGA-Out, 3D Sync-Out, USB Type A Power (5V/1.5A), RJ45, 12V Trigger, RS-232-In, Wired Remote-In, HDBaseT™, USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (WxDxH)	431 x 345 x 181mm
Weight	8.8kg (19.4lbs)
Available Colors	White
Noise Level	43dB/38dB (Normal/Eco. Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	540W (Normal Mode), 460W (Eco. Mode), <0.5W (Standby Mode), <2W (LAN Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Documentation Kit
Optional Accessories	Interchangeable Lens Options (x7)

*Note: Standard Lens
 ©2017 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.



Photos

